

SUPRA MB01/H 1PR LINE FRHF

Mic/Line Installation cable


Gauge: 1x3x0.24mm² / AWG 23

Rev.date: 2023-04-20

Customs tariff no: 8544499390

Country of origin: Sweden

- Excellent flame retardancy- Halogen free - low smoke
- Shielded for efficient noise rejection
- Low capacitance - low microphony
- Low mechanical friction jacket, perfect for installation



MB01/H FRHF - Halogen Free & Fire Retardant - Mic/Line cable

Supra MB-series - A durable, strong, flame resistant professional installation cable

The conductors of multi-strand tinned 5N purity copper, together with the PE di-electric (insulation) provides for a low capacitance professional installation cable with very good electrical properties. The Supra professional series of cables have been recognized as trustworthy partners on-stage and in studios for a long period of time. MB-01/H is a single channel analogue installation cable aimed for longer analogue transmissions in e.g. studios. Very good electrical and mechanical properties for a long service life. It can be used both as single-end as well as balanced, we recommend balanced operation at longer lengths (> 5 meters).

Halogen Free & Fire Retardant

Supra professional series are fire retardant and halogen-free allowing them to be used professionally in public spaces. As soon as there are large events where the public is present there are tough regulations on all parts when it comes to durability, fire resistance and emissions of toxic fumes in case of a fire.

CONSTRUCTION

Conductors (x2):	Tin plated Cu-wire OFC 5N 19x0.127 mm
Cross section Area:	2x0,24mm ² / AWG 23
Insulation:	PE, Blue & Red. Twisted pair.
Screen:	Alu/Pet foil
Screen coverage:	100%
Screen connection:	Tin plated OFC drain-wire 19x0.127mm
Jacket:	PE ECCOH 5943 FRHF, round
Jacket thickness.	1.5 mm
Diameter.	4.8 mm
Colour	Anthracite grey (other colours upon order)
Marking:	SUPRA MB01/H > Made in Sweden > Meter mark
Weight.	32 kg/km
Packing:	Bobbin 300m & 1000m (other lengths upon order)
Suitable plugs:	Supra RCA-6, RCA-6SC & Swift XLR



**FLAME
RETARDANT**



Dca-s1,d1
0402-CPR-7P04047-1
EN50399:2011 &
EN60332-1-2:2004/A1
:2015/A11:2016
www.supracables.se



ELECTRICAL SPECIFICATION

Resistance:	72 ohm/km
Capacitance:	52 pF/m

PRODUCT	Qty	Part.no	EAN-13	E-no
MB01/H 1PR LINE FRHF GREY B300	300M	1001800158	7330060002144	4866393
MB01/H 1PR LINE FRHF GREY B1000	1000M	1001800604	7330060207600	4867006