

## LORAD 2.5 SPC CS-20-US MAINS CORD SET

Silver plated & screened Mains Cord Set, 125V/20A


Gauge: 3x2.5mm<sup>2</sup> / AWG 13

Rev.date: 2022-08-30

Customs tariff no: 8544499500

Country of origin: Sweden

- Screened mains flex cable
- Gold plated Connectors
- Silver plated OFC wires - low loss construction
- Protects both from electric & magnetic fields.



### LoRad - Low Radiation - Silver Plated

Shielded cord set comprising Supra LoRad Silver plated 3x2.5 mm<sup>2</sup> cable, Supra SWF-16 female plug (IEC-320) & Supra SW-EU male plug. Current rating 20 A continuously. The US-version, with straight Nema plug, is the most common standard throughout America. Fits our LoRad mains power distribution blocks. LoRad means Low Radiation and the design of these mains flex cables minimises both electric & magnetic alternating fields. Allow your hi-fi gear the most welcome benefit of all, the possibility to be silent, when supposed to. Only then, the tiniest details and notes will become clearly audible. LoRad protects both from alternating fields radiating from the cable as well as from pick-up of surrounding airborne noise fields.

- Short pitch twisting of the lead cores cancels the magnetic alternating fields and will not infect adjacent interconnects with noise feedback.
- LoRad will result in a cleaner sound, better picture and a more healthy home and working environment with low levels of harmful fields.
- The screen protects your equipment from radiated mains, RF pick-up.

### CONSTRUCTION

Cable:	Lorad 3x2.5 SPC
Cross section area:	Silver plated OFC 3x2.5mm <sup>2</sup> / AWG 13
Screen:	Semi-conductive Nylon tape, black, 100%
Jacket:	PVC GA78, round
Diameter:	11mm
Cable colour:	Anthracite Grey (other colours upon order)
Marking:	SUPRA LORAD SPC 3G2.5 + Made in Sweden + Meter mark
Connectors:	SW-US Nema male to SWF-16 20A C19 IEC320 female plug
- Pin Material:	24K Gold plated Copper
- Pin connection:	Screw/clamp
- Colour:	Anthracite Grey
Cable direction:	Nema plug to Wall socket & SWF16 to device power inlet
Rated Voltage/current:	125V / 20A
Packing:	1-2m Blister 25x21.5x4.8cm, 4m Blister 31,5x25,4x6,0cm



Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. Lorad are tested and certified by Intertek Sweden, meeting the American ETL safety regulations & European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon order.

PRODUCT	Length	Qty	Part.no	EAN-13	Carton Weight
LORAD 2.5 SPC CS-20-US 1M	3.28ft	1PC	3002100372	7330060209239	25 0,37
LORAD 2.5 SPC CS-20-US 1.5M	4.92ft	1PC	3002100364	7330060209222	25 0,48
LORAD 2.5 SPC CS-20-US 2M	6.56ft	1PC	3002100380	7330060209246	25 0,58
LORAD 2.5 SPC CS-20-US 4M	13.12ft	1PC	3002100398	7330060209253	13 1,04

