

SUPRA CLASSIC 2X2.5/H FRHF

Loudspeaker cable - Flame retardant & halogen free


Gauge: 2x2.5mm² / AWG 13

Rev.date: 2022-08-30

Customs tariff no: 8544499390

Origin: Sweden

- Excellent flame-retardancy
- Halogen-free
- Low smoke generation
- Low toxic gas emission



Classic 2,5/H FRHF - Halogen free & flame retardant

Similar to the Supra Classic-series but with fire retardant and halogen free PE ECCOH (polyetylen) insulation. The cable is slightly stiffer than the standard Classic, yet easy-gliding insulation, perfect for in-wall installation in conduit pipes. For indoor/outdoor use. Tin-plated conductors for maximum corrosion protection. For outdoor use, installation in conduit pipes is recommended.

Approved for installation in public and official premises. We meet the latest regulation of flame retardancy and toxic emissions. Standard CPS; Construction Products Regulation; EN 50399:2011 and EN 60322-1-2:2004/A1:2015/A11:2016 CE marking; EN 50399 and EN60322.

Fire behavior:: DCA, Smoke protection: s1, Flaming droplets: d1, Reaction to fire classification: Dca-s1, d1

CONSTRUCTION

Conductor (x2):	Tin plated Copper wire 320x0.10 mm
Diameter:	2.4 mm
Cross section Area:	2x2.5mm ² / AWG 13
Insulation:	PE ECCOH 5943 FRHF, eight-model
Insulation thickness:	0.8 mm
External size:	3.6x7.4 mm
Colour:	Iceblue (other colours upon order)
Markning:	SUPRA Classic 2.5/H + Made in Sweden + Length marking
Weight:	66 kg/km
Packing:	Bobbin 200m (other lengths upon order)

ELECTRICAL SPECIFICATION

Resistance:.	6.8 ohm/km
Inductance	0.45 uH/m
Rated voltage:	80V



PRODUCT	Qty	Part.no	EAN-13	E-no
CLASSIC 2X2.5/H FRHF BLUE B200	200M	1000000248	7330060000218	4866703

Below are produced upon order:

CLASSIC 2X2.5/H FRHF GREY B200	200M	1000001121		
CLASSIC 2X2.5/H FRHF WHITE B200	200M	1000001162	7330060207143	
CLASSIC 2X2.5/H FRHF BLUE B1000	1000M	1000001196	7330060207730	4866996