

SUPRA CLASSIC 2X4.0/H FRHF

Loudspeaker cable - Flame retardant & halogen free


Gauge: 2x4.0mm² / AWG 11

Rev.date: 2022-08-30

Customs tariff no: 8544499390

Origin: Sweden

- Excellent flame-retardancy
- Halogen-free
- Low smoke generation
- Low toxic gas emission



Classic 4.0/H FRHF - Halogen free & flame retardant

Similar to the Supra Classic-series but with fire retardant and halogen free PE ECCOH (polyetylen) insulation. The cable is slightly stiffer than the standard Classic, yet easy-gliding insulation, perfect for in-wall installation in conduit pipes. For indoor/outdoor use. Tin-plated conductors for maximum corrosion protection. For outdoor use, installation in conduit pipes is recommended.

Approved for installation in public and official premises. We meet the latest regulation of flame retardancy and toxic emissions. Standard CPS; Construction Products Regulation; EN 50399:2011 and EN 60322-1-2:2004/A1:2015/A11:2016 CE marking; EN 50399 and EN60322.

Fire behavior:: DCA, Smoke protection: s1, Flaming droplets: d1, Reaction to fire classification: Dca-s1, d1

CONSTRUCTION

Conductor (x2): Tin plated Copper wire 511x0.10 mm

Diameter: 2.7 mm

Cross section Area: 2x4.0mm² / AWG 11

Insulation: PE ECCOH 5943 FRHF, eight-model

Insulation thickness: 1 mm

External size: 4.7x9.6 mm

Colour: Iceblue (other colours upon order)

Markning: SUPRA Classic 4.0/H + Made in Sweden + Length marking

Weight: 104 kg/km

Packing: Bobbin 100m (other lengths upon order)

ELECTRICAL SPECIFICATION

Resistance: 4.3 ohm/km

Inductance 0.55 uH/m

Rated voltage: 80V



PRODUCT	Qty	Part.no	EAN-13	E-no
CLASSIC 2X4.0/H FRHF BLUE B100	100 M	1000000735	7330060202902	4866822