

SUPRA RONDO 4X4.0

Twisted Loudspeaker cable


Gauge: 4x4.0mm² / AWG 11

Rev.date: 2022-08-30

Customs tariff no: 8544499390

Country of origin: Sweden

- Twisted - Highly flexible
- Low inductance
- Double insulated, approved for 100V systems
- Tin plated - Corrosion resistant



RONDO 4x4.0- Versatile, flexible and possible to Star Quad wiring

High quality speaker cable with four tin plated multi-strand conductors, high pitch twisted for optimal noise cancellation and lower inductance.

The Supra Rondo cable allows for a number of possible connections, where the full range Quad Star, is a nearly ideal laid out suppressing the inductance to low levels. Thanks to its four leads it is possible also to connect as bi-wired or bi-amplified. Tests have shown that full range Star Quad give the best conditions for a better transition of music. The production method we use allow us to twin with short pitch and still keep it resilient, persistent to handling fatigue, making it especially useful on-stage. Further to the Star Quad lead configuration, this short pitch twinning of the leads, contributes to even lower inductance and lowered tendency to pick-up RFI (Radio Frequency Interference, a single denomination of all high frequency electromagnetic fields. Any means to lower RFI in your hifi or multimedia equipment will undoubtedly pay off with lower noise floor and a much crisper and sharper picture as well as a sound full of micro dynamics standing out from a pitch black background, with a completely new level of bass attack and dynamic.

Star Quad connection



CONSTRUCTION

Conductor (x4):	Tin plated OFC-wire 511x0.10 mm
Diameter:	2.7 mm
Cross section Area:	4x4.0mm ² / AWG 11
Insulation:	Blue, white, black & red
Insulation thickness:	0.7 mm
Jacket:	PVC GA78, round
Jacket thickness:	1.5 mm
Diameter:	10.6 mm
Colour:	Iceblue & Anthracite grey (other colours upon order)
Marking:	SUPRA RONDO 4x4.0 + Made in Sweden + Meter mark
Weight:	230 kg/km
Packing:	Bobbin 50m (other lengths upon order) & blister 5m & 10m



ELECTRICAL SPECIFICATION

Resistance:	4.3 ohm/km
Inductance:	0.38 uH/m (star quad connection lower to 0.35 uH/m)
Rated voltage:	100V

PRODUCT	Qty	Part.no	EAN-13	E-no	Carton
RONDO 4X4.0 GREY B50	50M	1000000057	7330060000119	4866283	
RONDO 4X4.0 BLUE B50	50M	1000000305	7330060000249	4866911	
Blister pack:					
RONDO 4X4.0 BLUE 5M	1PC	1000000479	7330060201905		13pcs
RONDO 4X4.0 BLUE 10M	1PC	1000000602	7330060202667		13pcs