

## SUPRA DAC-SL AUDIO

High end Analogue Stereo interconnect with RCA-plugs

Gauge: 1x3x0.24mm<sup>2</sup> / AWG 23

Rev.date: 2026-03-11

Customs tariff no: 8544429010

Country of origin: Sweden



- An ultra fast, dynamic & neutral interconnect - with great 3D sound stage
- Low capacitance - signal pulse without flattening or slowing down
- Shielded with efficient and strong semi-conductive nylon
- Robust & lockable connectors - noise immune and gold plated

### DAC-SL 2RCA-2RCA Audio - A lightning-fast interconnect cable with no brakes

High end analogue interconnect with lockable RCA-plugs

Supra DAC is a really rapid response interconnect thanks to its extremely low capacitance. In accordance with our design philosophy, the inductance must be low for a loudspeaker cable whereas for a signal interconnect the capacitance must be kept to a minimum. Supra DAC is insulated with a special PE plastic which exhibits only 45 pF/m. Further it is foamed and encloses a lot of the cheapest, yet most efficient insulation; Air. More correctly insulation should be denominated dielectricum according to the physical laws, where there actually does not exist anything called insulation. Every substance, gas, fluid or solid, exhibits electrical properties, where the trick is to find and choose the most benign. Air is easily available, cheap and shows very good dielectrical properties compared to its price. When the PE is foamed, the residual amount of PE becomes like a sponge, hence further reducing its electrical influence on the fragile music signal. The enclosed air becomes the major dielectricum and results in an electrical locomotion without brakes; full dynamics, response time and 3D sound stage, you simply will not come any closer to the real live experience. Further it is shielded with our very efficient and strong semi-conductive nylon ribbon, keeping all malicious noise out. The velocity factor of SUPRA DAC is as high as 78% of the speed of light. With the PTFE/Teflon, often used among our competitors, it would have been only 71%.

Application examples are mid- to high-end analogue interconnect equipped with Supra RCA or XLR plugs. DAC-SL is equipped with 24K heavy-duty goldplated connector PPSL.

### CONSTRUCTION

Cable:	SUPRA DAC
Jacket:	PVC GA78, round
Diameter:	6.1mm
Colour:	Ice blue (other colours upon request)
Marking:	SUPRA DAC > Made in Sweden > Meter mark
Screen connection:	Semi-balanced, the screen is only conneted in the source end.
Plugs:	SUPRA PPSL, 2 RCA male > 2 RCA male
- Material:	24K Gold plated Copper, chuck lock (turn the chassis to fasten & release)
- Colour:	Anthraccite grey
- Locking:	Chuck lock at device & cable
Solder tin:	Almit SR34 Super
Signal direction:	Follow the arrows printed on the cable > source > receiver
Packing:	Blister 25 x 21.5 x 4.8cm

! Plugs with chuck lock. Turn the grey housing to release or lock the plug to the female terminal.



Special lengths are made upon request.

PRODUCT	Qty	Part.no	EAN-13	E-no	Crt Weight
DAC-SL AUDIO BLUE PAIR 75CM	1PAIR	1001900099	7330060003066	6243020	25 0,30
DAC-SL AUDIO BLUE PAIR 1M	1PAIR	1001901295	7330060053450		25 0,31
DAC-SL AUDIO BLUE PAIR 2M	1PAIR	1001901188	7330060053467		25 0,40