

SUPRA DAC-XLR AUDIO

High end Analogue Stereo interconnect with XLR-plugs

Gauge: 1x3x0.24mm² / AWG 23

Rev.date: 2026-03-11

Customs tariff no: 8544429010

Country of origin: Sweden



- Low capacitance - signal pulse without flattening or slowing down
- An ultra fast, dynamic & neutral interconnect - with great 3D sound stage
- Shielded with efficient and strong semi-conductive nylon
- Robust & lockable connectors - noise immune and gold plated

DAC-XLR 2XLR-2XLR Audio - A lightning-fast interconnect cable with no brakes

Supra DAC is a really rapid response interconnect thanks to its extremely low capacitance. In accordance with our design philosophy, the inductance must be low for a loudspeaker cable whereas for a signal interconnect the capacitance must be kept to a minimum. Supra DAC is insulated with a special PE plastic which exhibits only 45 pF/m. Further it is foamed and encloses a lot of the cheapest, yet most efficient insulation; Air. More correctly insulation should be denominated dielectricum according to the physical laws, where there actually does not exist anything called insulation. Every substance, gas, fluid or solid, exhibits electrical properties, where the trick is to find and choose the most benign. Air is easily available, cheap and shows very good dielectrical properties compared to its price. When the PE is foamed, the residual amount of PE becomes like a sponge, hence further reducing its electrical influence on the fragile music signal. The enclosed air becomes the major dielectricum and results in an electrical locomotion without brakes; full dynamics, response time and 3D sound stage, you simply will not come any closer to the real live experience. Further it is shielded with our very efficient and strong semi-conductive nylon ribbon, keeping all malicious noise out. The velocity factor of SUPRA DAC is as high as 78% of the speed of light. With the PTFE/Teflon, often used among our competitors, it would have been only 71%.

Application examples are mid- to high-end analogue interconnect equipped with Supra RCA or XLR plugs. DAC-XLR is equipped with 24K heavy-duty goldplated connector Swift.

CONSTRUCTION

Cable:	SUPRA DAC
Mantel:	PVC GA78, round, Diameter 6.1mm
Colour:	Ice blue (other colours upon request)
Marking:	SUPRA DAC > Made in Sweden > Meter mark
Screen connection:	Balanced connection, the screen is connected in both ends
Plugs:	Supra Swift XLR , fully shielded & very robust construction
- Type:	2 XLR 3F female red/black > 2 XLR 3M male red/black
- Pin material:	24K Gold plated OFC
- Colour:	Anthracite grey
- Locking:	Snap lock at device & screw clamp at the cable
Solder tin:	Almit SR34 Super
Signal direction:	Follow the arrows printed on the cable > source > receiver
Packing:	Blister 25 x 21.5 x 4.8cm



Special lengths are made upon request.



PRODUCT	Qty	Part.no	EAN-13	E-no	Crt Weight
DAC-XLR AUDIO BLUE PR 75CM	1PAIR	1001900180	7330060003134	6243024	25 0,41
DAC-XLR AUDIO BLUE PAIR 1M	1PAIR	1001901337	7330060053535		25 0,42
DAC-XLR AUDIO BLUE PAIR 2M	1PAIR	1001901220	7330060053542		25 0,52