



Product Safety Sheet for Supra DAC-SL Audio Cables

Product Name: Supra DAC-SL Audio

Manufacturer Information:

Name: Supra Cables / Jenving Technology AB

Address: Bastbacka 112-113, 45991 Ljungskile, Sweden

Contact: Jörgen Wahlsberg, +46-522-698990, www.supracables.se

1. Product Description

Product Type: High-speed analog RCA interconnect cable designed for audiophiles, ideal for connecting high-fidelity equipment such as CD players, DACs (Digital-to-Analogue Converters), pre-amplifiers, and power amplifiers. Engineered for unmatched signal clarity, precision, and rapid transient response, the Supra DAC-SL delivers lifelike sound with depth and a dynamic, three-dimensional soundstage.

Applications: Ideal for high-fidelity Hi-Fi, studio, and home theater systems, the Supra DAC-SL preserves every musical detail with ultra-low capacitance, air-foamed PE insulation, and semi-conductive nylon shielding. It delivers clear, uncolored sound with precise timing, superior RFI protection, and reliable performance via Supra PPSL RCA connectors.

2. Safety Standards and Compliance

Relevant Directives and Standards:

- Low Voltage Directive (LVD) 2014/35/EU
- RoHS Directive 2011/65/EU
- General Product Safety Regulation (GPSR) 2023/988
- CE Marking: This product conforms to all applicable EU safety, health, and environmental protection standards and bears the CE marking.

3. Risk Assessment and Mitigation

Potential Hazards:

- Electrical Shock: Risk if the cables are damaged or improperly installed.
- Fire Hazard: Reduced compared to standard cables, but proper installation is required to maintain flame-retardant properties.
- Physical Damage: Risk of damage to the cables if subjected to excessive bending, crushing, or abrasion.

Mitigation Measures:

- Manufactured with tin-plated oxygen-free copper (OFC) for high conductivity and corrosion resistance
- Halogen-free insulation reduces toxic smoke and fumes in case of fire.
- Flame-retardant (FRHF) properties comply with EN 60332-1 and EN 50575 standards.
- Clearly marked for correct usage and cross-sectional area.

4. Technical Specifications

- Conductor Material: Tin-plated oxygen-free copper (OFC)
- Purity: 5N (99.999% pure copper)
- Available Cross-Sectional Area: 0.24 mm² (AWG 23)
- Insulation Material: Gas-foamed polyethylene (PE) Rated Voltage: 80 V

5. Labeling and Traceability

Each product is labeled with:

- Product Name
- Serial/Batch Number
- Manufacturer Contact Information
- Meter Markings for length measurement
- CE Marking

6. Instructions for Safe Use

- Ensure the cable is suitable for the intended audio application and power requirements.
- Install according to local building and fire safety codes, particularly in public or commercial spaces.
- Avoid exceeding the cable's current-carrying capacity to prevent overheating.
- Inspect for physical damage before installation; do not use if the insulation is compromised.
- For in-wall or conduit installations, verify flame-retardant performance requirements.

7. Incident Management and Reporting

Post-Market Surveillance:

- Supra Cables monitors product performance and user feedback to identify potential safety issues.

Incident Reporting:

- In case of a safety issue, customers are encouraged to contact Supra Cables immediately.
- Incidents will be reported to relevant authorities via the EU Safety Business Gateway as required by GPSR.


8. Declaration of Conformity

Supra Cables declares that this product complies with the following directives and standards:

- CE, RoHS, REACH & CPR verified by Rise

9. Disposal Instructions

- Dispose of this product in accordance with local electronic waste disposal regulations.
- Do not discard with general household waste.



Signed by: Jörgen Wahlsberg
Date: 2026-03-11

