



## Product Safety Sheet for Supra DAC-XLR Digital Cables

Product Name: Supra DAC-XLR Digital

Manufacturer Information:

Name: Supra Cables / Jenving Technology AB

Address: Bastbacka 112-113, 45991 Ljungskile, Sweden

Contact: Jörgen Wahlsberg, +46-522-698990, [www.supracables.se](http://www.supracables.se)

### 1. Product Description

Product Type: The Supra DAC-XLR is a high-performance analog XLR balanced interconnect cable designed for audiophiles and professional audio systems. It connects DACs, CD players, preamplifiers, power amplifiers, and other components with balanced XLR inputs and outputs. Engineered for ultra-low capacitance, fast transient response, and balanced signal design, it delivers precise, lifelike sound with a stable three-dimensional sound-stage. Its PE-foam dielectric and semi-conductive nylon shielding minimize interference, while durable 24K gold-plated Supra Swift XLR connectors ensure reliable, consistent connectivity.

Applications: Ideal for high-fidelity Hi-Fi systems, professional recording studios, and home theater setups using balanced audio connections, the Supra DAC-XLR preserves every musical detail, providing clean, dynamic, and interference-free audio performance with accurate timing and depth.

### 2. Safety Standards and Compliance

Relevant Directives and Standards:

- Low Voltage Directive (LVD) 2014/35/EU
- RoHS Directive 2011/65/EU
- General Product Safety Regulation (GPSR) 2023/988
- CE Marking: This product conforms to all applicable EU safety, health, and environmental protection standards and bears the CE marking.

### 3. Risk Assessment and Mitigation

Potential Hazards:

- Electrical Shock: Risk if the cables are damaged or improperly installed.
- Fire Hazard: Reduced compared to standard cables, but proper installation is required to maintain flame-retardant properties.
- Physical Damage: Risk of damage to the cables if subjected to excessive bending, crushing, or abrasion.

Mitigation Measures:

- Manufactured with tin-plated oxygen-free copper (OFC) for high conductivity and corrosion resistance
- Halogen-free insulation reduces toxic smoke and fumes in case of fire.
- Flame-retardant (FRHF) properties comply with EN 60332-1 and EN 50575 standards.
- Clearly marked for correct usage and cross-sectional area.

### 4. Technical Specifications

- Conductor Material: Tin-plated oxygen-free copper (OFC)
- Purity: 5N (99.999% pure copper)
- Cross-Sectional Area: 0.24 mm<sup>2</sup> (AWG 23)

- Insulation Material: Gas-foamed polyethylene (PE)
- Rated Voltage: 80 V
- Connector Type: 24K gold-plated Supra Swift XLR

## 5. Labeling and Traceability

Each product is labeled with:

- Product Name
- Serial/Batch Number
- Manufacturer Contact Information
- Meter Markings for length measurement
- CE Marking

## 6. Instructions for Safe Use

- Ensure the cable is suitable for the intended audio application and power requirements.
- Install according to local building and fire safety codes, particularly in public or commercial spaces.
- Avoid exceeding the cable's current-carrying capacity to prevent overheating.
- Inspect for physical damage before installation; do not use if the insulation is compromised.
- For in-wall or conduit installations, verify flame-retardant performance requirements.

## 7. Incident Management and Reporting

Post-Market Surveillance:

- Supra Cables monitors product performance and user feedback to identify potential safety issues.

Incident Reporting:

- In case of a safety issue, customers are encouraged to contact Supra Cables immediately.
- Incidents will be reported to relevant authorities via the EU Safety Business Gateway as required by GPSR.

## 8. Declaration of Conformity

Supra Cables declares that this product complies with the following directives and standards:

- CE, RoHS, & REACH verified by Rise

## 9. Disposal Instructions

- Dispose of this product in accordance with local electronic waste disposal regulations.
- Do not discard with general household waste.



Signed by: Jörgen Wahlsberg  
Date: 03/12/2026

