

Product Safety Sheet for Supra DVI CABLES


Product Name: Supra DVI-DVI DUAL-LINK CABLES

Manufacturer Information:

Name: Supra Cables / Jenving Technology AB

Address: Bastbacka 112-113, 45991 Ljungskile, Sweden

Contact: Jörgen Wahlsberg, +46-522-698990, www.supracables.se



1. Product Description

Product Type: High-quality DVI-DVI Dual Link digital video cable designed for high-resolution digital signal transmission between computers, displays, projectors and other DVI-compatible devices.

Applications: This cable is intended for high-bandwidth digital video transfer in professional and consumer AV systems. Suitable for connecting computers, graphics cards, monitors, projectors and display systems requiring Dual Link DVI performance, including high-resolution and 3D video applications.

2. Safety Standards and Compliance

Relevant Directives and Standards:

- Low Voltage Directive (LVD) 2014/35/EU
- RoHS Directive 2011/65/EU
- General Product Safety Regulation (GPSR) 2023/988
- CE Marking: This product conforms to all applicable EU safety, health, and environmental protection standards and bears the CE marking.

3. Risk Assessment and Mitigation

Potential Hazards:

- Electrical Shock: Risk if the cables are damaged or improperly installed.
- Fire Hazard: Reduced compared to standard cables, but proper installation is required to maintain flame-retardant properties.
- Physical Damage: Risk of damage to the cables if subjected to excessive bending, crushing, or abrasion.

Mitigation Measures:

- Manufactured with tin-plated oxygen-free copper (OFC) for high conductivity and corrosion resistance
- Clearly marked for correct usage and cross-sectional area.

4. Technical Specifications

- Cable Type: DVI-D Dual Link digital video cable
- Connector Type: DVI-D 24+1 male to DVI-D 24+1 male
- Conductor Material: 5N oxygen-free copper (OFC)
- Conductor Insulation: Air-injected PE foam
- Shielding: Triple shielding with individually screened twisted pairs plus overall aluminum foil and copper braid shielding for EMI/RFI protection
- Connector Housing: Fully shielded aluminum housing
- Connector Plating: 24K gold plated contacts
- Cable Diameter: 11 mm

- Jacket Material: PVC GA78
- Colour: Ice Blue

5. Labeling and Traceability

Each product is labeled with:

- Product Name
- Serial/Batch Number
- Manufacturer Contact Information
- Meter Markings for length measurement
- CE Marking

6. Instructions for Safe Use

- Ensure the cable is suitable for the intended audio application and power requirements.
- Install according to local building and fire safety codes, particularly in public or commercial spaces.
- Avoid exceeding the cable's current-carrying capacity to prevent overheating.
- Inspect for physical damage before installation; do not use if the insulation is compromised.
- For in-wall or conduit installations, verify flame-retardant performance requirements.

7. Incident Management and Reporting

Post-Market Surveillance:

- Supra Cables monitors product performance and user feedback to identify potential safety issues.

Incident Reporting:

- In case of a safety issue, customers are encouraged to contact Supra Cables immediately.
- Incidents will be reported to relevant authorities via the EU Safety Business Gateway as required by GPSR.


8. Declaration of Conformity

Supra Cables declares that this product complies with the following directives and standards:

- CE, RoHS, REACH & CPR verified by Rise

9. Disposal Instructions

- Dispose of this product in accordance with local electronic waste disposal regulations.
- Do not discard with general household waste.



Signed by: Jörgen Wahlsberg
Date: 05/07/2026

