

LINC 2X2.5

Screened Loudspeaker cable


Gauge: 2x2.5mm² / AWG 13

Rev.date: 2026-04-08

Customs tariff no: 8544499390

Country of origin: Sweden

- Screened - less pick-up noise
- Low inductance
- Double insulated, approved for 100V systems
- Tin plated - corrosion resistant



LINC 2x2.5 - Screened

The Supra Linc is an evolution of the Supra Round Two-part cable, Rondo, taking the already low magnetic field levels even further through short-pitch twinning. Supra Linc has been enhanced with a shielding layer that blocks electric fields, particularly preventing the pickup of harmful RFI (radio frequency interference), whether analogue or digital. Its low inductance ensures excellent transient response and signal transparency. The name “Linc” stands for Low Interaction Concept. The cable is highly flexible, making it suitable for permanent in-wall installations, including conduit runs.

The sonic benefits are immediately noticeable: a lower noise floor and enhanced system dynamics. This is especially evident in micro-dynamics—the subtle nuances in music, like the precise attack of a drumstick, tiny shifts in phrasing, or delicate tonal variations. These subtle details, which give music its natural life and prevent it from sounding artificial, emerge clearly against a pitch-black background, free from noise. For many music lovers, this is a remarkable discovery.

CONSTRUCTION

Conductor (x2):	Tin plated OFC-wire 320x0.10 mm
Diameter:	2.3 mm
Cross section Area:	2x2.5mm ² / AWG 13
Insulation:	Red + & Black -
Insulation thickness:	0.7 mm
Screen:	Alu/PET foil, 100%
Screen connection:	Tin plated OFC drain wire 19x0.127mm
Jacket:	PVC GA78, round
Jacket thickness:	1.5 mm
Diameter:	8.1 mm
Colour:	Ice blue (other colours upon request)
Marking:	SUPRA LINC 2x2.5 + Made in Sweden + Meter mark
Weight:	94 kg/km
Packaging:	Bobbin 100m (other lengths upon order)

Drain Wire / Shield (Earth) Connection
The earth conductor should be connected in the source end only (amplifier side) to:

1. Earth terminal at the amp (if available)
2. Connect to any of the amp chassis screws.
3. Negative speaker out terminal

ELECTRICAL SPECIFICATION

Resistance:	6.8 ohm/km
Inductance:	0.40 uH/m
Rated voltage:	100V



PRODUCT	Qty	Part.no	EAN-13	E-no
LINC 2X2.5 BLUE B100	100M	1000000180	7330060000140	4866583