

LORAD 1.5 CS-BS MAINS CORD SET

Tin plated & screened Mains Cord Set, 250V/13A

Gauge: 3x1.5mm² / AWG 15

Rev.date: 2026-03-31

Customs tariff no: 8544499500

Country of origin: Sweden

- Screened mains flex cable - low radiation
- Gold plated onnectors
- Tin plated OFC wires - Corrosion resistant
- Protects both from electric & magnetic fields




LoRad - Low Radiation

Shielded power cord set comprising Supra LoRad 3x1.5 mm² cable, Supra SWF-10 female connector (IEC 60320), and Supra MC-BS male plug (BS 1363). The cable is rated for continuous currents up to 16 A and is designed for use with British and Irish 13 A mains outlets. It is compatible with Supra LoRad power distribution blocks (up to 6 outlets) and suitable for hi-fi and multimedia equipment using standard IEC 60320 connections.

- LoRad (Low Radiation) technology is designed to reduce both electric and magnetic field emissions. The tightly twisted conductors help minimise magnetic field radiation, while the shielding reduces interference from external electromagnetic and radio-frequency (RF) noise.
- This construction helps limit interference between power cables and nearby signal cables, supporting stable operation of connected equipment.

CONSTRUCTION

Cable:	Lorad 3x1.5
Cross section area:	Tin plated OFC 3x1.5mm ² / AWG 15
Screen:	Semi-conductive Nylon tape, black, coverage 100%, drain wire
Jacket:	PVC GA78, round. D=9.5mm
Cable colour:	Ice Blue (other colours upon special order)
Marking:	SUPRA LORAD 3G1.5 + Made in Sweden + Meter mark
Connectors:	MC-BS male with 13A fuse to SWF-10s 10A C13 IEC320 female plug
- Pin Material:	24K Gold plated Copper Alloy
- Pin connection:	Screw/clamp
- Colour:	Ice blue / Anthracite Grey
Cable direction:	MC-BS plug to wall socket & SWF10 to device power inlet
Rated Voltage/current:	250V / 13A fuse
Packaging:	1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm



Supra SWF-10

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the British safety regulations & European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon order.



PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 1.5 CS-BS 1M	1PC	3004100222	7330060009129	25	0,33
LORAD 1.5 CS-BS 1.5M	1PC	3004100123	7330060205552	25	0,38
LORAD 1.5 CS-BS 2M	1PC	3004100172	7330060009136	25	0,43
LORAD 1.5 CS-BS 4M	1PC	3004100230	7330060200014	13	0,74