

LORAD 2.5 CS-16-BS MAINS CORD SET

Tin plated & screened Mains Cord Set, 250V/16A

Gauge: 3x2.5mm² / AWG 13

Rev.date: 2023-08-14

Customs tariff no: 8544499500

Country of origin: Sweden

- Screened mains flex cable - low radiation
- Gold plated Connectors
- Tin plated OFC wires - Corrosion resistant
- Protects both from electric & magnetic fields.



LoRad - Low Radiation

Shielded mains cord set with Supra LoRad 3x2.5 mm² cable, Supra SWF-16 IEC-320 female connector, and Supra MC-BS male plug for BS 1363 (13 A) sockets. Rated for continuous currents up to 16 A. Compatible with Supra LoRad power distribution blocks (6+ outlets) and IEC-320 equipped hi-fi and multimedia devices.


- LoRad (Low Radiation) technology is designed to reduce both electric and magnetic field emissions. The tightly twisted conductors help minimise magnetic field radiation, while the shielding reduces interference from external electromagnetic and radio-frequency (RF) noise.
- This construction helps limit interference between power cables and nearby signal cables, supporting stable operation of connected equipment.

CONSTRUCTION

Cable:	Lorad 3x2.5
Cross section area:	Tin plated OFC 3x2.5mm ² / AWG 13
Screen:	Semi-conductive nylon tape, black, coverage 100%, drain wire
Jacket:	PVC GA78, round. D=11mm
Cable colour:	Ice blue (other colours upon request)
Marking:	SUPRA LORAD 3G2.5 + Made in Sweden + Meter mark
Connectors:	MC-BS male with 13A fuse to SWF-16 16A C19 IEC320 female plug
- Pin Material:	24K Gold plated copper alloy
- Pin connection:	Screw/clamp
- Colour:	Ice blue / Anthracite grey
Cable direction:	MC-BS plug to wall socket & SWF16 to device power inlet
Rated Voltage/current:	250V / 16A / 13A fuse
Packaging:	1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the British safety regulations & European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon order.



PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 2.5 CS-16-BS 1M	1PC	3004100560	7330060205590	25	0,37
LORAD 2.5 CS-16-BS 1.5M	1PC	3004100578	7330060205606	25	0,48
LORAD 2.5 CS-16-BS 2M	1PC	3004100586	7330060205613	25	0,58
LORAD 2.5 CS-16-BS 4M	1PC	3004100594	7330060205620	13	1,04