

## LORAD 2.5 CS-BS MAINS CORD SET

Tin plated & screened Mains Cord Set, 250V/13A

Gauge: 3x2.5mm<sup>2</sup> / AWG 13

Rev.date: 2026-04-02

Customs tariff no: 8544499500

Country of origin: Sweden

- Screened mains flex cable - low radiation
- Gold plated connectors
- Tin plated OFC wires - Corrosion resistant
- Protects both from electric & magnetic fields



### LoRad - Low Radiation

This high-performance cord set includes a Supra LoRad 3x2.5mm<sup>2</sup> cable, Supra SWF-10 female connector (IEC-320), and Supra MC-BS male plug. Rated for continuous current up to 16 A, it fits British & Irish 13 A sockets and Supra LoRad mains distribution blocks with up to six outlets. "LoRad" (Low Radiation) design minimizes both electrical and magnetic fields, reducing interference and allowing your hi-fi or multimedia system to operate in an electrically silent environment, revealing subtle musical and visual details.

- Twisted conductors cancel magnetic fields, preventing interference with nearby cables.
- Shielded design protects equipment from radiated mains and RF noise.
- Cleaner audio & video with reduced EM pollution for a healthier home or workspace.
- Compatible with 10–13 A IEC-320 devices; related LoRad 2.5 CS-16-BS cord set rated at 16 A.

### CONSTRUCTION


Cable:	Lorad 3x2.5
Cross section area:	Tin plated OFC 3x2.5mm <sup>2</sup> / AWG 13
Screen:	Semi-conductive Nylon tape, black, coverage 100%, drain wire
Jacket:	PVC GA78, round. D=11mm
Cable colour:	Ice blue (other colours upon request)
Marking:	SUPRA LORAD 3G2.5 + Made in Sweden + Meter mark
Connectors:	MC-BS male with 13A fuse to SWF-10s 10A C13 IEC320 female plug
- Pin Material:	24K Gold plated Copper Alloy
- Pin connection:	Screw/clamp
- Colour:	Ice blue / Anthracite grey
Cable direction:	MC-BS plug to wall socket & SWF10 to device power inlet
Rated Voltage/current:	250V / 13A fuse
Packaging:	1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm

Supra SWF-16



LoRad 2.5 CS-16-BS

Supra SWF-10



LoRad 2.5 CS-BS

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the British safety regulations & European safety regulation HD21.5 S3. Standard lengths as below, special length cables upon request.



PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 2.5 CS-BS 1M	1PC	3004100511	7330060205569	25	0,37
LORAD 2.5 CS-BS 1.5M	1PC	3004100529	7330060205552	25	0,48
LORAD 2.5 CS-BS 2M	1PC	3004100537	7330060205583	25	0,58
LORAD 2.5 CS-BS 4M	1PC	3004100545	7330060205576	13	1,04