

LORAD 2.5 SPC CS-US MAINS CORD SET

Silver plated & screened Mains Cord Set, 125V/15A


Gauge: 3x2.5mm² / AWG 13

Rev.date: 2026-04-08

Customs tariff no: 8544499500

Country of origin: Sweden

- Screened mains flex cable
- Gold plated Connectors
- Silver plated OFC wires - low loss construction
- Protects both from electric & magnetic fields.



LoRad - Low Radiation - Silver Plated

Shielded cord set comprising Supra LoRad Silver plated 3x2.5 mm² cable, Supra SWF-10s female plug (IEC-320) & Supra SW-EU male plug. Current rating 15 A continuously. The US-version, with straight Nema plug, is the most common standard throughout America. Fits our LoRad mains power distribution blocks. LoRad means Low Radiation and the design of these mains flex cables minimises both electric & magnetic alternating fields. Allow your hi-fi gear the most welcome benefit of all, the possibility to be silent, when supposed to. Only then, the tiniest details and notes will become clearly audible. LoRad protects both from alternating fields radiating from the cable as well as from pick-up of surrounding airborne noise fields.

- Short pitch twisting of the lead cores cancels the magnetic alternating fields and will not infect adjacent interconnects with noise feedback.
- LoRad will result in a cleaner sound, better picture and a more healthy home and working environment with low levels of harmful fields.
- The screen protects your equipment from radiated mains, RF pick-up.

CONSTRUCTION

Cable: Lorad 3x2.5 SPC
 Cross section area: Silver plated OFC 3x2.5mm² / AWG 13
 Screen: Semi-conductive nylon tape, black, 100%
 Jacket: PVC GA78, round
 Diameter: 11mm
 Cable color: Anthracite grey (other colors upon request)
 Marking: SUPRA LORAD SPC 3G2.5 + Made in Sweden + Meter mark
 Connectors: SW-US Nema male to SWF-10s 10A C13 IEC320 female plug
 - Pin Material: 24K gold plated copper
 - Pin connection: Screw/clamp
 - Color: Anthracite grey
 Cable direction: Nema plug to wall socket & SWF10 to device power inlet
 Rated Voltage/current: 125V / 15A
 Packing: 1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm



Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. Lorad are tested and certified by Intertek Sweden, meeting the American ETL safety regulations & European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon request.



PRODUCT	Length	Qty	Part.no	EAN-13	Carton Weight
LORAD 2.5 SPC CS-US 1M	3.28ft	1PC	3004100941	7330060206955	25 0,37
LORAD 2.5 SPC CS-US 1.5M	4.92ft	1PC	3004100958	7330060206962	25 0,48
LORAD 2.5 SPC CS-US 2M	6.56ft	1PC	3004100966	7330060206979	25 0,58
LORAD 2.5 SPC CS-US 4M	13.12ft	1PC	3004100974	7330060206986	13 1,04