

SUPRA MB04/H 4PRS LINE FRHF

Mic/Line Installation cable - 4 pairs


Gauge: 4x 3x0.24mm² / AWG 23

Rev.date: 2026-07-22

Customs tariff no: 8544499390

Country of origin: Sweden

- Low capacitance - low microphony
- Excellent flame retardancy- Halogen free - low smoke
- Separate shields for efficient noise rejection
- Low mechanical friction jacket, perfect for installation



MB04/H FRHF - Halogen Free & Fire Retardant - Mic/Line stereo cable

Supra MB-series - A durable, strong, flame resistant professional installation cable

The conductors of multi-strand tinned 5N purity copper, together with the PE di-electric (insulation) provides for a low capacitance professional installation cable with very good electrical properties. The Supra professional series of cables have been recognized as trustworthy partners on-stage and in studios for a long period of time. MB-04/H is a dual channel analogue installation cable aimed for longer analogue transmissions in e.g. studios. Very good electrical and mechanical properties for a long service life. It can be used both as single-end as well as balanced, we recommend balanced operation at longer lengths (> 5 meters).

Halogen Free & Fire Retardant

Supra professional series are fire retardant and halogen-free allowing them to be used professionally in public spaces. As soon as there are large events where the public is present there are tough regulations on all parts when it comes to durability, fire resistance and emissions of toxic fumes in case of a fire.

CONSTRUCTION

Conductors (x2):	Tin plated Cu-wire OFC 5N 19x0.127 mm
Cross section Area:	4x 2x0.24mm ² / AWG 23
Insulation:	PE, Blue & Red. Twisted pair
Screen:	Alu/Pet foil
Screen coverage:	100%
Screen connection:	Tin plated OFC drain-wire 19x0.127mm
Parts:	4 twisted pairs, PE jacket with coloured yarn for easy identification
Jacket:	PE ECCOH 5943 FRHF, round
Jacket wall thickness:	1.5 mm
Diameter:	8 mm
Colour:	Anthracite grey (other colours upon request)
Marking:	SUPRA MB04/H > Made in Sweden > Meter mark
Weight:	72 kg/km
Packaging:	Bobbin 100m (other lengths upon request)
Suitable plugs:	Supra RCA-6, RCA-6SC & Swift XLR

ELECTRICAL SPECIFICATION

Resistance: 72 ohm/km

Capacitance: 52 pF/m



PRODUCT	Qty	Part.no	EAN-13	E-no
MB04-JP/H 4PRS LINE FRHF GREY B100	100M	1001800182	7330060002168	4866413