

SUPRA RONDO 4X4.0

Twisted Loudspeaker cable


Gauge: 4x4.0mm² / AWG 11

Rev. date: 2026-05-18

Customs tariff no: 8544499390

Country of origin: Sweden



- Twisted - Highly flexible
- Low inductance
- Double insulated, approved for 100V systems
- Tin-plated - Corrosion resistant



RONDO 4x4.0- Versatile, flexible and possible to Star Quad wiring

High-quality speaker cable with four tin-plated multi-strand conductors, tightly twisted with short pitch geometry for effective noise cancellation and very low inductance. The Supra Rondo cable supports multiple connection options, including full-range Star Quad, bi-wire, and bi-amplified configurations. In Star Quad mode, the conductors are arranged in an optimized geometry that significantly reduces inductance and ensures excellent signal integrity. This configuration provides ideal conditions for natural and accurate music reproduction, with improved transient response and overall clarity. The production method allows for tight twisting while maintaining high flexibility and excellent resistance to mechanical fatigue, making the cable particularly well suited for both fixed installations and demanding stage use. In addition to the Star Quad geometry, the short-pitch twisting further reduces inductance and minimizes susceptibility to RFI (Radio Frequency Interference) and other high-frequency electromagnetic disturbances. Lowering RF interference in audio systems results in a reduced noise floor, improved detail resolution, sharper imaging, and more precise micro-dynamics, with bass transients that are cleaner and more controlled.

CONSTRUCTION

Conductor (x4):	Tin-plated OFC-wire 511x0.10 mm	<p>Star Quad connection</p> 
Diameter:	2.7 mm	
Cross section Area:	4x4.0mm ² / AWG 11	
Insulation:	Blue, White, Black & Red	
Insulation thickness:	0.7 mm	
Jacket:	PVC GA78, round	
Jacket thickness:	1.5 mm	
Diameter:	10.6 mm	
Colour:	Ice Blue & Anthracite grey (other colours upon order)	
Marking:	SUPRA RONDO 4x4.0 + Made in Sweden + Meter mark	
Weight:	230 kg/km	
Packaging:	Bobbin 50m (other lengths upon request) & 5m & 10m	

ELECTRICAL SPECIFICATION

Resistance:	4.3 ohm/km
Inductance:	0.38 uH/m (star quad connection lower to 0.35 uH/m)
Rated voltage:	100V



PRODUCT	Qty	Part.no	EAN-13	E-no	Carton
RONDO 4X4.0 GREY B50	50M	1000000057	7330060000119	4866283	
RONDO 4X4.0 BLUE B50	50M	1000000305	7330060000249	4866911	
RONDO 4X4.0 BLUE 5M	1PC	1000000479	7330060201905		13pcs
RONDO 4X4.0 BLUE 10M	1PC	1000000602	7330060202667		13pcs