

SUPRA TRICO 1BNC-1BNC DIGITAL


Digital SDI S/PDIF 75 Ohm

Gauge: Triax 0.71mm² / AWG 19

Rev. date: 2026-05-28

Customs tariff no: 8544499390

Country of origin: Sweden



- True 75 Ohm – matches 75 Ohm transmission lines without losses
- Exceptionally low attenuation – enables long cable runs with preserved signal integrity
- PE foam insulation – extremely low capacitance for optimal digital signal transfer
- Silver-plated OFC conductors – excellent high-frequency conductivity and improved signal transmission stability

Trico 1BNC-1BNC - Digital Interconnect SDI & S/PDIF – 75 Ohm

The Supra Trico true 75 Ohm digital interconnects are engineered for high-performance digital audio and video transmission applications requiring precise characteristic impedance and exceptional bandwidth. They are ideally suited for connections between computers and DACs, CD transports and DACs, AV amplifiers, and SDI video systems, ensuring accurate signal transfer with outstanding integrity.

Designed with extremely low capacitance and optimized bandwidth, Supra Trico cables deliver stable transmission of digital square waves while maintaining excellent headroom, even across longer cable runs. The result is reliable, low-jitter performance with maximum signal fidelity.

The Supra Trico-BNC is a single-ended interconnect specifically designed for SDI applications, as well as digital audio connections between CD transports, DACs, and AV amplifiers.

CONSTRUCTION

Cable:	SUPRA Trico
Jacket:	PVC GA78, round
Diameter:	8.3mm
Colour:	Ice Blue (other colours upon request)
Marking:	SUPRA Trico > Made in Sweden > Meter mark
Shield connection:	Semi-balanced, the outer screen is only connected at the source end
Connectors:	Neutrik BNC NBLC75BSX14
- Type:	1 BNC male > 1 BNC male
- Material:	Pins of 24K gold-plated OFC
- Colour:	Silver/black
- Locking:	Twist-lock
Solder tin:	Almit SR34 Super
Signal direction:	Follow the arrows > Source > Receiver
Packaging <3m:	23x20x2.2 cm
Packaging 8m:	31x28x4.3 cm



Special lengths are made upon request.

PRODUCT	Qty	Part.no	EAN-13	E-no	Crt Weight
TRICO 1BNC-1BNC DIGITAL 0.5M	1PC	1001910379	7330060210495		25 0,30
TRICO 1BNC-1BNC DIGITAL 1M	1PC	1001900354	7330060003370	6243085	25 0,35
TRICO 1BNC-1BNC DIGITAL 2M	1PC	1001901105	7330060063329		25 0,43
TRICO 1BNC-1BNC DIGITAL 8M	1PC	1001910510	7330060210969		16 1,50