

LORAD 2.5 EXCALIBUR CS-20-US MAINS CORD SET

Rhodium plated & Double screened Mains Cord Set, 250V/16A

Gauge: 3x2.5mm² / AWG 13


Rev.date: 2026-04-02

Customs tariff no: 8544499500

Country of origin: Sweden

- Double screened mains flex cable – Excalibur Rhodium Edition
- Rhodium plated connectors
- Silver plated OFC wires – low loss construction
- Protects both from electric & magnetic fields

20A

**LoRad - Low Radiation - Silver Plated**

Shielded cord set comprising Supra LoRad 2.5 Excalibur Silver-Plated OFC cable with rhodium-plated NEMA-20 20 A male plug and rhodium-plated IEC320 C19 20 A female connector. Rated for continuous 20 A. The US version, with straight NEMA-20 plug, fits standard outlets throughout North America. Compatible with Supra LoRad mains power distribution blocks. SUPRA LoRad Excalibur represents the pinnacle of our power cable design. Built for the most demanding high-end audio and AV systems, it combines silver-plated conductors, dual-layer shielding (aluminium + semiconductive), and rhodium-plated connectors to deliver power with unmatched purity, stability, and minimal noise.

“LoRad” (Low Radiation) design minimizes both electric and magnetic alternating fields, while twisted conductor geometry cancels magnetic fields and prevents interference with adjacent cables. The dual shielding ensures a near noise-free environment, revealing the finest musical details and dynamics.

LoRad Excalibur ensures cleaner sound, tighter dynamics, and a more stable electrical environment. The shielding protects equipment from radiated mains disturbances and RF interference, providing ultimate performance for high-end systems.

CONSTRUCTION

| | |
|------------------------|--|
| Cable: | LoRad 2.5 EXCALIBUR |
| Cross section area: | 5N OFC, 5% silver 3x2.5mm ² / AWG 13 |
| Screen: | Alu/PET foil + Semi-conductive nylon |
| Jacket: | PVC GA78, round |
| Diameter: | 11mm |
| Cable colour: | Ice Blue Metallic |
| Marking: | SUPRA LORAD EXCALIBUR 3X2.5 + Made in Sweden + Meter mark |
| Connectors: | NEMA-20 20 A Rhodium male plug to IEC320 C19 20 A Rhodium female connector |
| - Pin Material: | Rhodium plated copper |
| - Pin connection: | Screw/clamp |
| - Colour: | Matching cable finish |
| Cable direction: | Follow the arrows > Wall socket > Power inlet |
| Rated Voltage/current: | 125 V / 20 A / 2500 W |
| Packaging: | 1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm |

Note: The plug must be connected to a grounded wall socket for the full LoRad effect. LoRad cables are tested and certified by Intertek Sweden, meeting American safety standards. Standard lengths available; special lengths upon request.



| PRODUCT | Qty | Part.no | EAN-13 | Carton | Weight |
|-----------------------------------|-----|------------|---------------|--------|--------|
| LORAD 2.5 EXCALIBUR CS-20-US 1M | 1PC | 3004101311 | 7330060211324 | 25 | 0,47 |
| LORAD 2.5 EXCALIBUR CS-20-US 1.5M | 1PC | 3004101303 | 7330060211317 | 25 | 0,55 |
| LORAD 2.5 EXCALIBUR CS-20-US 2M | 1PC | 3004101337 | 7330060211348 | 25 | 0,65 |
| LORAD 2.5 EXCALIBUR CS-20-US 2.5M | 1PC | 3004101329 | 7330060211331 | 25 | 0,73 |
| LORAD 2.5 EXCALIBUR CS-20-US 3M | 1PC | 3004101345 | 7330060211355 | 13 | 0,82 |
| LORAD 2.5 EXCALIBUR CS-20-US 4M | 1PC | 3004101352 | 7330060211362 | 13 | 0,99 |