

LORAD 2.5 EXCALIBUR CS-US MAINS CORD SET

Rhodium plated & Double screened Mains Cord Set, 250V/15A


Gauge: 3x2.5mm² / AWG 13

Rev.date: 2026-04-07

Customs tariff no: 8544499500

Country of origin: Sweden

- Double screened mains flex cable – Excalibur Rhodium Edition
- Rhodium plated connectors
- Silver plated OFC wires – low loss construction
- Protects both from electric & magnetic fields

**LoRad - Low Radiation - Silver Plated**

Shielded cord set comprising the Supra LoRad 2.5 Excalibur Silver Plated cable, equipped with a rhodium-plated SW-US mains plug male and a rhodium-plated SWF-16 IEC320 C19 female connector. Rated for 15 A continuous current at 125 V. The CS-US version is designed for the North American market, featuring a US-standard grounded plug compatible with outlets in the United States and other regions using the same format. It is suitable for use with Supra LoRad power distribution blocks rated up to 15 A. SUPRA LoRad Excalibur represents the pinnacle of power cable design, developed for the most demanding high-end audio and AV systems. By combining silver-plated oxygen-free copper conductors, advanced dual-layer shielding, and rhodium-plated connectors, it delivers exceptionally clean and stable power. “LoRad” stands for Low Radiation, referring to a design that minimizes both electric and magnetic alternating fields. The Excalibur version enhances this further with aluminium foil shielding and a semiconductive layer, along with optimized conductor geometry to achieve extremely low noise and maximum performance. This enables your hi-fi equipment to operate in a near noise-free environment, revealing greater detail, improved dynamics, and enhanced clarity.

- Short pitch twisting of the lead cores cancels magnetic alternating fields and prevents interference with adjacent cables.
- LoRad Excalibur results in a cleaner sound, improved dynamics, and a more stable electrical environment with minimal interference.
- The dual shielding protects your equipment from radiated mains disturbances and RF interference.

CONSTRUCTION

Cable:	LoRad 3x2.5 EXCALIBUR
Cross section area:	5N OFC, 5% silver 3x2.5mm ² / AWG 13
Screen:	Alu/PET foil + Semi-conductive Nylon
Jacket:	PVC GA78, round
Diameter:	11mm
Cable colour:	Ice Blue Metallic
Marking:	SUPRA LORAD EXCALIBUR 3X2.5 + Made in Sweden + Meter mark
Connectors:	SW-US, rhodium-plated male to IEC320 C15 Rhodium female
- Pin Material:	Rhodium plated copper
- Pin connection:	Screw/clamp
- Colour:	Black
Cable direction:	Follow the arrows > Wall socket > Power inlet
Rated Voltage/current:	125V / 15A
Packaging:	1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm

Note: The plug must be connected to a grounded wall socket for the full LoRad effect. LoRad cables are tested and certified by Intertek Sweden, meeting American safety standards. Standard lengths available; special lengths upon request.



PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 2.5 EXCALIBUR CS-EU 1M	1PC	3004101105	7330060211096	25	0,47
LORAD 2.5 EXCALIBUR CS-EU 1.5M	1PC	3004101097	7330060211089	25	0,55
LORAD 2.5 EXCALIBUR CS-EU 2M	1PC	3004101113	7330060211102	25	0,65
LORAD 2.5 EXCALIBUR CS-EU 2.5M	1PC	3004101121	7330060211119	25	0,73
LORAD 2.5 EXCALIBUR CS-EU 3M	1PC	3004101139	7330060211126	13	0,82
LORAD 2.5 EXCALIBUR CS-EU 4M	1PC	3004101147	7330060211133	13	0,99