

**LORAD 2.5 EXCALIBUR CS-AUS/NZ MAINS CORD SET**

Rhodium plated &amp; Double screened Mains Cord Set, 250V/10A


Gauge: 3x2.5mm<sup>2</sup> / AWG 13

Rev.date: 2026-04-02

Customs tariff no: 8544499500

Country of origin: Sweden

- Double screened mains flex cable – Excalibur Rhodium Edition
- Rhodium plated connectors
- Silver plated OFC wires – low loss construction
- Protects both from electric & magnetic fields

**LoRad - Low Radiation - Silver Plated**

Shielded cord set comprising Supra LoRad 2.5 Excalibur Silver-Plated OFC cable with rhodium-plated AS/NZS 3112 male plug and rhodium-plated IEC320 C15 female connector. Rated for continuous 10 A / 250 V. The Australian/New Zealand version, with straight AS/NZS plug, fits standard outlets throughout these regions. Compatible with Supra LoRad mains power distribution blocks.

SUPRA LoRad Excalibur represents the pinnacle of our power cable design. Built for the most demanding high-end audio and AV systems, it combines silver-plated conductors, dual-layer shielding (aluminium + semiconductive), and rhodium-plated connectors to deliver power with unmatched purity, stability, and minimal noise.

- “LoRad” (Low Radiation) design minimizes both electric and magnetic alternating fields, while twisted conductor geometry cancels magnetic fields and prevents interference with adjacent cables.
- The dual shielding ensures a near noise-free environment, revealing the finest musical details and dynamics.

**CONSTRUCTION**

Cable:	LoRad 3x2.5 EXCALIBUR
Cross section area:	5N OFC, 5% silver 3x2.5mm <sup>2</sup> / AWG 13
Screen:	Alu/PET foil + Semi-conductive Nylon
Jacket:	PVC GA78, round
Diameter:	11mm
Cable colour:	Ice Blue Metallic
Marking:	SUPRA LORAD EXCALIBUR 3X2.5 + Made in Sweden + Meter mark
Connectors:	AS/NZS 3112 Male Rhodium to IEC320 C15 Rhodium Female 10 A
- Pin Material:	Rhodium plated copper
- Pin connection:	Screw/clamp
- Colour:	Black
Cable direction:	Follow the arrows > Wall socket > Power inlet
Rated Voltage/current:	250 V / 10 A / 2500 W
Packaging:	1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the European safety regulation HD21.5 S3. Standard lengths as below, special length cables upon request.



PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 2.5 EXCALIBUR CS-EU 1M	1PC	3004101386	7330060211386	25	0,47
LORAD 2.5 EXCALIBUR CS-EU 1.5M	1PC	3004101378	7330060211379	25	0,55
LORAD 2.5 EXCALIBUR CS-EU 2M	1PC	3004101394	7330060211393	25	0,65
LORAD 2.5 EXCALIBUR CS-EU 2.5M	1PC	3004101410	7330060211416	25	0,73
LORAD 2.5 EXCALIBUR CS-EU 3M	1PC	3004101402	7330060211409	13	0,82
LORAD 2.5 EXCALIBUR CS-EU 4M	1PC	3004101428	7330060211423	13	0,99