

LORAD 2.5 EXCALIBUR CS-16-CH MAINS CORD SET

Rhodium plated & Double screened Mains Cord Set, 250V/16A

Gauge: 3x2.5mm² / AWG 13


Rev.date: 2026-04-02

Customs tariff no: 8544499500

Country of origin: Sweden

- Double screened mains flex cable – Excalibur Rhodium Edition
- Rhodium plated connectors
- Silver plated OFC wires – low loss construction
- Protects both from electric & magnetic fields

16A

**LoRad - Low Radiation - Silver Plated**

Shielded cord set comprising Supra LoRad 2.5 Excalibur Silver-Plated OFC cable with rhodium-plated Swiss Type J male plug and rhodium-plated IEC320 C19 female connector. Rated for continuous 10 A. The Swiss version, with straight Type J plug, fits standard outlets throughout Switzerland. Compatible with Supra LoRad mains power distribution blocks. SUPRA LoRad Excalibur represents the pinnacle of our power cable design. Built for the most demanding high-end audio and AV systems, it combines silver-plated conductors, dual-layer shielding (aluminium + semi-conductive), and rhodium-plated connectors to deliver power with unmatched purity, stability, and minimal noise.

“LoRad” (Low Radiation) design minimizes both electric and magnetic alternating fields, while twisted conductor geometry cancels magnetic fields and prevents interference with adjacent cables. The dual shielding ensures a near noise-free environment, revealing the finest musical details and dynamics.

LoRad Excalibur ensures cleaner sound, tighter dynamics, and a more stable electrical environment. The shielding protects equipment from radiated mains disturbances and RF interference, providing ultimate performance for high-end systems.

CONSTRUCTION

Cable:	LoRad 2.5 EXCALIBUR
Cross section area:	5N OFC, 5% silver 3x2.5mm ² / AWG 13
Screen:	Alu/PET foil + Semi-conductive nylon
Jacket:	PVC GA78, round
Diameter:	11mm
Cable colour:	Ice Blue Metallic
Marking:	SUPRA LORAD EXCALIBUR 3X2.5 + Made in Sweden + Meter mark
Connectors:	Swiss Type J Rhodium male plug to IEC320 C19 Rhodium female connector
- Pin Material:	Rhodium plated copper
- Pin connection:	Screw/clamp
- Colour:	Matching cable finish
Cable direction:	Follow the arrows > Wall socket > Power inlet
Rated Voltage/current:	250V / 16A
Packaging:	1-2m: 25x21.5x4.8cm, 4m: 31.5x25.4x6.0cm

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the European safety regulation HD21.5 S3. Standard lengths as below, special length cables upon request.



PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 2.5 EXCALIBUR CS-16-CH 1M	1PC	3004101592	7330060211560	25	0,47
LORAD 2.5 EXCALIBUR CS-16-CH 1.5M	1PC	3004101584	7330060211553	25	0,55
LORAD 2.5 EXCALIBUR CS-16-CH 2M	1PC	3004101618	7330060211584	25	0,65
LORAD 2.5 EXCALIBUR CS-16-CH 2.5M	1PC	3004101600	7330060211577	25	0,73
LORAD 2.5 EXCALIBUR CS-16-CH 3M	1PC	3004101626	7330060211591	13	0,82
LORAD 2.5 EXCALIBUR CS-16-CH 4M	1PC	3004101634	7330060211607	13	0,99